

Technical data



	50 XL	50 XL High Intensive	50 XL IP Control	50 XLc	50 XLc High Intensive*	50 SLI	50 SLI High Intensive*	50 SLI IP Control
Tubes	50x120 W	50x180 W	50xIP Control	50x120 W	50x180 W	42x120 W 8x80 W	42x180 W 8x140 W	50 x IP Control
Face tanner	-	-	-	integrated	integrated	4 x 400 W	4 x 400 W	4 x 400 W
SPS filter	-	-	-	-	-	●	●	●
HPS filter	-	-	-	-	-	○	○	○
Surface	Metallic-effect	Metallic-effect	Metallic-effect	Metallic-effect	Metallic-effect	Metallic-effect	Metallic-effect	Metallic-effect
Floor lighting	●	●	●	●	●	●	●	●
DecoLight	●	●	●	●	●	●	●	●
Stand-by inside lighting	●	●	●	●	●	●	●	●
2 Doors open synchronous	●	●	●	●	●	●	●	●
Digital timerdisplay	●	●	●	●	●	●	●	●
Internal timer	●	●	●	●	●	●	●	●
Connection for external timer	●	●	●	●	●	●	●	●
Adjustable bodycooler: 1-2	●	●	●	●	●	●	●	●
Lift system	○	○	○	○	○	○	○	○
Qsens (4 nozzles)	○	○	○	○	○	○	○	○
Xsens	○	○	○	○	○	○	○	○
Loudspeakers	●	●	●	●	●	●	●	●
SoundAround	○	○	○	○	○	○	○	○
MyMP3	○	○	○	○	○	○	○	○
SmartVoice	○	○	○	○	○	○	○	○
Hour counter resetable	●	●	●	●	●	●	●	●
Hour counter non-resetable	●	●	●	●	●	●	●	●
Connection	400 V/3N ~/PE/50 Hz	400 V/3N ~/PE/50 Hz	400 V/3N ~/PE/50 Hz	400 V/3N ~/PE/50 Hz	400 V/3N ~/PE/50 Hz	400 V/3N ~/PE/50 Hz	400 V/3N ~/PE/50 Hz	400 V/3N ~/PE/50 Hz
Power	6.8 kW	11.5 kW	11 kW	6.8 kW	11.5 kW	8.5 kW	13 kW	13.4 kW
Fuses	3 x 16A	3x 20A	3 x 16A	3 x 16A	3 x 20A	3 x 20A	3 x 25A	3 x 25A
Weight (excl. Packaging)	600 kg	650 kg	500 kg	600 kg	650 kg	625 kg	675 kg	525 kg



● As standard ○ Optional * Intensive-variant with 180 W tubes with long spot and 800 h recommended lifetime

Available colours:
Royal Red
Pearl White in the variations:
Passion, Romance, Cool

Specifications are subject to change without notice.

